



Notified Body 1020

CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

No. 1020 – CPR – 010033469

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

CERAMIC BRICKS

category I according to the EN 771-1:2011+A1:2015
Type: see annex N1 to the certificate -2 pages

placed on the market under the name or trade mark of

LLC “LSR. Wall Materials”

187330, Leningrad region, Kirov district,
Otradnoye, 55, Nikolskoye highway,
Russian Federation
VAT No. 4706035757

and produced in the manufacturing plant:

Nikolsky Brick Factory

187330, Leningrad region, Kirov district, Otradnoye, 55 Nikolskoye highway,
Russian Federation
VAT No. 4706035757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 771-1:2011+A1:2015

under system 2+ are applied and that

the factory production control is assessed to be in conformity with the applicable requirements

This certificate was first issued on 04 July 2014 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

Stamp of the Notified Body 1020

Prague, 31 May 2017



Ing. Iveta Jiroutova
Deputy Manager of the Notified Body



TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p.
Technical and Test Institute for Construction Prague, SOE

Akreditovaná zkušební laboratoř, Autorizovaná osoba, Notifikovaná osoba, Oznamovaný subjekt, Subjekt pro technické posuzování, Certifikační orgán, Inspekční orgán / Accredited Testing Laboratory, Authorized Body, Notified Body, Technical Assessment Body, Certification Body, Inspection Body. Prosecká 811/76a, 190 00 Praha 9 - Prosek, Czech Republic

Appendix No.1 to Certificate No. 1020 – CPR – 010033469

Product range manufactured by “LSR. Wall Materials” LLC

«Nikolsky Brick Factory»

Euro facade clinker brick 0,7NS; Standard hollow facing brick 1 NS; Euro hollow common brick 0,7 NS; Standard hollow common brick 1NS; Standard solid facing brick 1 NS; Standard solid common brick 1NS; Standard solid facing brick R60 1 NS; Standard solid common brick R60 1NS; 0,54NS Clinker solid brick; 0,54NS Hollow brick clinker; 0,54 NS Hollow common brick; 0,54 NS Solid common brick; 0,7NS Euro facade clinker solid brick; 0,7NS Solid common brick;

(colour range – red, dark red, brown, dark brown, straw-yellow, cream-coloured, white, gray, ivory)

Porous ceramic brick 1 NS; Porous ceramic block 2,146 NS; Tongue-and-groove porous ceramic block 10,7 NS; Tongue-and-groove porous ceramic block 11,2 NS;

Tongue-and-groove porous ceramic block 14,3 NS;

Name of the product	Type	Group according EN 1996-1-1	Bond strength, N/mm ² (EN 998-2)	Dimensions, mm	Tolerances of the mean value	Range	Mean compressive strength, mPa	Category	Gross dry density, kg/m ³	Tolerances	Water absorption, max. %	Durability	Active soluble salts content	Reaction to the fore
Euro facade clinker brick	U	1	0,15	250x85x65	T2	R2	30,0	I	1800	D2	5	F2	S2	A1
Standard hollow facing brick	U	2	0,15	250x120x65	T2	R2	18,0	I	1350	D2	7	F1	S2	A1
Euro hollow common brick	P	1	0,15	250x85x65	T1	R1	15,0	I	1800	D1	8	F1	S1	A1
Standard hollow common brick	P	2	0,15	250x120x65	T1	R1	15,0	I	1350	D1	8	F1	S1	A1
Standard solid facing brick	U	1	0,15	250x120x65	T2	R2	50,0	I	2200	D2	7	F1	S2	A1
Standard solid common brick	P	1	0,15	250x120x65	T1	R1	25,0	I	2200	D1	8	F1	S1	A1
Standard solid hollow facing brick R60	U	1	0,15	250x120x65	T2	R2	50,0	I	2200	D2	7	F1	S2	A1
Standard solid hollow brick R60	P	1	0,15	250x120x65	T1	R1	25,0	I	2200	D1	8	F1	S1	A1
Clinker solid brick	U	1	0,15	210x100x50	T2	R2	40,0	I	2250	D2	5	F2	S2	A1
Hollow brick clinker	U	1	0,15	210x100x50	T2	R2	30,0	I	1850	D2	5	F2	S2	A1
Hollow common brick	P	1	0,15	210x100x50	T1	R1	15,0	I	1850	D1	8	F1	S1	A1

Stamp of the Notified Body 1020

Prague, 31 May 2017



Ing. Iveta Jiroutova

Ing. Iveta Jiroutova
Deputy Manager of the Notified Body



® TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p.
Technical and Test Institute for Construction Prague, SOE

Akreditovaná zkušební laboratoř, Autorizovaná osoba, Notifikovaná osoba, Oznamovaný subjekt, Subjekt pro technické posuzování, Certifikační orgán, Inspekční orgán / Accredited Testing Laboratory, Authorized Body, Notified Body, Technical Assessment Body, Certification Body, Inspection Body. Prosecká 811/76a, 190 00 Praha 9 - Prosek, Czech Republic

Appendix No.1 to Certificate No. 1020 – CPR – 010033469

Name of the product	Type	Grade according EN 1996-1-1	Bond strength, N/mm ² (EH 998-2)	Dimensions, mm	Tolerances of the mean value	Range	Mean compressive strength, mPa	Category	Gross dry density, kg/m ³	Tolerances	Water absorption, max. %	Durability	Active soluble salts content	Reaction to the fire
Solid common brick	P	1	0,15	210x100x50	T1	R1	25,0	I	2250	D1	8	F1	S1	A1
Euro facade clinker solid brick	U	1	0,15	250x85x65	T2	R2	40,0	I	2200	D2	5	F2	S2	A1
Standard solid hollow brick	P	1	0,15	250x85x65	T1	R1	25,0	I	2200	D1	8	F1	S1	A1
Porous ceramic brick	P	2	0,15	250x120x65	T2	R1	15,0	I	1000	D1	-	F0	S2	A1
Porous ceramic block	P	2	0,15	250x120x140	T2	R1	15,0	I	900	D1	-	F0	S0	A1
Tongue-and-groove porous ceramic block	P	2	0,15	250x380x219	T1	R1	10,0	I	800	D1	-	F0	S0	A1
Tongue-and-groove porous ceramic block	P	2	0,15	398x250x219	T1	R1	10,0	I	800	D1	-	F0	S0	A1
Tongue-and-groove porous ceramic block	P	2	0,15	250x510x219	T1	R1	10,0	I	800	D1	-	F0	S0	A1

Stamp of the Notified Body 1020

Prague, 31 May 2017



Ing. Iveta Jiroutova
Deputy Manager of the Notified Body